## (19) World Intellectual Property Organization International Bureau



### 

# (43) International Publication Date 18 January 2001 (18.01.2001)

**PCT** 

# (10) International Publication Number WO 01/04963 A1 √

- (51) International Patent Classification7: 33/00, H05B 33/00, H05K 5/02
- HOIL 31/12.
- (21) International Application Number: PCT/SG99/00073
- (22) International Filing Date: 9 July 1999 (09.07.1999)
- (25) Filing Language:

English

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): OSRAM OPTO SEMICONDUCTORS GMBH & CO. OHG [DE/DE]; Wernerwerskstrasse 2, D-93049 Regensburg (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): GUENTHER, Ewald, Karl, Michael [DE/SG]: 991 Bukit Timah Road #03-11, Maplewoods, Singapore 589630 (SG).


- (74) Agent: EPPING, Wilhelm; Epping Hermann & Fischer GbR. Postfach 12 10 26, D-80034 München (DE).
- (81) Designated States (national): AE. AL, AM, AT. AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, Cl, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published:

- With international search report.

[Continued on next page]

(54) Title: ENCAPSULATION OF A DEVICE



(57) Abstract: An encapsulation for an electrical device (100) is disclosed. A cap support (130) is provided in the non-active regions (120) of the device (100) to prevent the package from contacting the active components (110) of the device due to mechanical stress induced in the package.

30

### Abstract

An encapsulation for an electrical device is disclosed. A cap support is provided in the non-active regions of the device to prevent the package from contacting the active components of the device due to mechanical stress induced in the package.